

# CHAPTER 7

---

## EMISSIONS OF FLUORINATED SUBSTITUTES FOR OZONE DEPLETING SUBSTANCES

[Parts shaded in grey – the unchanged text from the 2006 IPCC Guidelines]

[Bracketed text – characterization of guidance as new, updated, and/or elaborated]

Authors

Paul Ashford (UK)

James A. Baker (USA), Denis Clodic (France), Sukumar Devotta (India), David Godwin (USA), Jochen Harnisch (Germany), William Irving (USA), Mike Jeffs (Belgium), Lambert Kuijpers (Netherlands), Archie McCulloch (UK), Roberto De Aguiar Peixoto (Brazil), Shigehiro Uemura (Japan), and Daniel P. Verdonik (USA)

Kathrine Loe Bjønness (Norway), Barbara Gschrey (Germany), Tomas Gustafsson (Sweden), Junichi Ishikawa (Japan), Michela Maione (Italy)

Contributing Authors

William G. Kenyon (USA), Sally Rand (USA), and Ashley Woodcock (UK)

Roberto Peixoto (Brazil), Winfried Schwarz (Germany)

26

## Contents

27	7	Emissions of Fluorinated Substitutes for Ozone Depleting Substances .....	7.5
28	7.1	Introduction .....	7.5
29	7.1.1	Chemicals and relevant application areas covered .....	7.5
30	7.1.2	General methodological issues for all ODS substitute applications .....	7.7
31	7.1.2.1	Overview of ODS substitute issues .....	7.7
32	7.1.2.2	Choice of method .....	7.7
33	7.1.2.3	Choice of emission factors .....	7.9
34	7.1.2.4	Choice of activity data .....	7.9
35	7.1.2.5	Completeness .....	7.9
36	7.1.2.6	Developing a consistent time series .....	7.9
37	7.1.3	Uncertainty assessment .....	7.9
38	7.1.4	Quality Assurance/Quality Control (QA/QC), Reporting and Documentation for all ODS	
39		substitutes applications .....	7.9
40	7.2	Solvents (Non-Aerosol) .....	7.10
41	7.3	Aerosols (Propellants and Solvents) .....	7.10
42	7.4	Foam blowing agents .....	7.10
43	7.5	Refrigeration and Air Conditioning .....	7.11
44	7.5.1	Chemicals covered in this application area .....	7.11
45	7.5.2	Methodological issues .....	7.11
46	7.5.2.1	Choice of method .....	7.11
47	7.5.2.2	Choice of emission factors .....	7.17
48	7.5.2.3	Choice of activity data .....	7.19
49	7.5.2.4	Applying tier 2 methods – the example of mobile air conditioning (MAC) .....	7.21
50	7.5.2.5	Completeness .....	7.24
51	7.5.2.6	Developing a consistent time series .....	7.24
52	7.5.3	Uncertainty assessment .....	7.24
53	7.5.4	Quality Assurance/Quality Control (QA/QC), Reporting and Documentation .....	7.24
54	7.6	Fire Protection .....	7.25
55	7.7	Other applications .....	7.25
56	References	.....	7.26

57

58

## Tables

59	Table 7.1 (Updated)	Main application areas for HFCs and PFCs as ODS substitutes .....	7.6
60	Table 7.3 (Unchanged)	Example distribution of HFC/PFC use by application area (2002) .....	7.8
61	Table 7.3a (New)	Distribution of HFC use by application area for 2015 .....	7.8

62	Table 7.3b (New)	HFC consumption for Refrigeration and air conditioning in article 5 parties,	
63		percent of total by substance and sub-application area for 2015 .....	7.8
64	Table 7.3c (New)	HFC consumption for Refrigeration and air conditioning in article 5 parties,	
65		percent of Total by manufacturing and servicing for 2015 .....	7.9
66	Table 7.9 (Updated)	Default Estimates for charge, lifetime and emission factors for refrigeration	
67		and air-conditioning systems .....	7.18
68	Table 7. 9a (New)	German study 2015: emission factors for refrigeration and air-conditioning	
69		systems .....	7.19

## Boxes

71	Box 7.2A (New)	How to build a RAC inventory in a few simple steps_- Tier 1 and 2 Emission	
72		Factor Approaches.....	7.12
73	Box 7.2b (New)	Overview of the basic elements of the RAC refrigerant bank .....	7.13
74	Box 7.2c (New)	How to build the bank of ODS-substitutes in RAC .....	7.16
75	Box 7.3 (Unchanged)	Accounting for imports and exports of refrigerant and equipment .....	7.19
76	Box 7.3a (New)	Common data sources for the ODS-substitutes inventory .....	7.20
77	Box 7.4 (Updated)	Example of the application of a Tier 2a calculation for mobile air conditioning	7.21

# 7 EMISSIONS OF FLUORINATED SUBSTITUTES FOR OZONE DEPLETING SUBSTANCES

## 7.1 INTRODUCTION

### 7.1.1 Chemicals and relevant application areas covered

Hydrofluorocarbons (HFCs) and, to a very limited extent, perfluorocarbons (PFCs), are serving as alternatives to ozone depleting substances (ODS) being phased out under the Montreal Protocol. Current and expected application areas of HFCs and PFCs include (IPCC/TEAP, 2005):

- refrigeration and air conditioning;
- fire suppression and explosion protection;
- aerosols;
- solvent cleaning;
- foam blowing; and
- other applications<sup>1</sup>.

These major groupings of current and expected usage are referred to in this chapter as *applications* within the ODS substitutes category. This introduction (Section 7.1) provides a general framework for estimating emissions from ODS substitutes, and subsequent sections (Sections 7.2 through 7.7) provide more specialised guidance on the individual applications introduced above. Some of these applications themselves encompass products or uses with diverse emission characteristics, and countries will produce more rigorous estimates if they account for this diversity through the adoption of disaggregated assessments (higher tier). Additionally, the use of HFCs and PFCs in some applications, specifically rigid foam (typically closed-cell foam), refrigeration and fire suppression, can lead to the development of long-lived *banks* of material. The emission patterns from these uses can be particularly complex and methods employing disaggregated data sets are essential to generate accurate emissions estimates. Other applications, such as aerosols and solvent cleaning may have short-term inventories of stock but, in the context of emission estimation, can still be considered as sources of prompt emission. This statement also applies to flexible foams (typically open-cell foam).

[Update/Elaboration]

Since the 2006 IPCC Guidelines were finalized, a major change has occurred in the policy framework regulating HFCs. Formerly, HFCs, which do not directly deplete O<sub>3</sub>, were not regulated under the Montreal Protocol. However, during the 28th meeting of the parties (MOP28) held in Kigali (Rwanda) in October 2016, 197 countries adopted an amendment to phase down HFCs. The parties committed to cut the GWP-weighted production and consumption of HFCs by more than 80 percent over the next 30 years. Developed countries will begin reducing HFC consumption in 2019 and developing countries will follow with a freeze of HFC consumption levels between 2024 and 2028. A small group including the world's hottest countries (India, Pakistan, Iran, Saudi Arabia and Kuwait) will freeze HFC use by 2028. These production and consumption limits are expected to drive changes in the quantities and types of HFCs used in ODS substitute applications. To ensure that their HFC emissions inventories remain accurate, inventory compilers should familiarize themselves with the HFC limits in their countries and plan to gather data on the associated changes in HFC use and emissions.

HFCs are chemicals containing only hydrogen, carbon, and fluorine. Prior to the Montreal Protocol and the phase-out of various ODS, the only HFCs produced were HFC-152a, which is a component of the refrigerant blend R-500, and HFC-23, a low temperature refrigerant which is a by-product of HCFC-22<sup>2</sup> production. HFC-134a entered production in 1991 and a variety of other HFCs have since been introduced and are now being used as ODS substitutes (IPCC/TEAP, 2005) among other applications. When collecting data on HFC and PFC

<sup>1</sup> HFCs and PFCs may also be used as ODS substitutes in sterilisation equipment, for tobacco expansion applications, and as solvents in the manufacture of adhesives, coating and inks.

<sup>2</sup> HCFCs - hydrochlorofluorocarbons.

consumption for reporting purposes, care needs to be taken to include those HFCs in blends, but, at the same time, to avoid including those components of a blend which are not required to be reported (e.g., CFCs and HCFCs).

HFCs and PFCs have high global warming potentials (GWPs) and, in the case of PFCs, long atmospheric residence times. Table 7.1 gives an overview of the most important HFCs and PFCs (IPCC Second Assessment Report (IPCC, 1996); IPCC Third Assessment Report (IPCC, 2001); IPCC/TEAP, 2005), including their main application areas. The various HFCs and PFCs have very different potencies as greenhouse gases. PFCs have particularly high GWPs regardless of the integrated time horizon adopted because of their long atmospheric lifetimes. The consumption patterns relating to individual gases must be known, therefore, or estimated with reasonable accuracy, to achieve useful assessments for the contribution to global warming from emissions of these groups of chemicals.

As CFCs, halons, carbon tetrachloride, methyl chloroform, and, ultimately, HCFCs are being finally phased out<sup>3</sup>, HFCs are being selectively used as replacements. PFCs are also being used, but only to a limited extent. Even though up to 75 percent of previous application of CFC may now be covered by non fluorocarbon technologies (IPCC/TEAP, 2005), HFC use is expected to continue to grow at least in the short term.

[Update/Elaboration – Table 7.1]

TABLE 7.1 (UPDATED)							
MAIN APPLICATION AREAS FOR HFCs AND PFCs AS ODS SUBSTITUTES 1							
Chemical	Refrigeration and Air Conditioning	Fire Suppression and Explosion Protection	Aerosols		Solvent Cleaning	Foam Blowing	Other Applications <sup>2</sup>
			Propellants	Solvents			
HFC-23	X	X					
HFC-32	X						
HFC-125	X	X					
HFC-134a	X	X	X			X	X
HFC-143a	X						
HFC-152a	X		X			X	
HFC-227ea	X	X	X			X	X
HFC-236fa	X	X					
HFC-245fa	X			X		X	
HFC-365mfc				X	X	X	
HFC-43-10mee				X	X		
PFC-14 <sup>3</sup> (CF <sub>4</sub> )		X					
PFC-116 (C <sub>2</sub> F <sub>6</sub> )							X
PFC-218 (C <sub>3</sub> F <sub>8</sub> )							
PFC-31-10 (C <sub>4</sub> F <sub>10</sub> )		X					
PFC-51-14 <sup>4</sup> (C <sub>6</sub> F <sub>14</sub> )					X		X
Source:							
<sup>1</sup> Several applications use HFCs and PFCs as components of blends. The other components of these blends are sometimes ODSs and/or non-greenhouse gases. Several HFCs, PFCs and blends are sold under various trade names; only generic designations are used in this chapter.							
<sup>2</sup> Other applications include sterilisation equipment, tobacco expansion applications, plasma etching of electronic chips (PFC-116) and as solvents in the manufacture of adhesive coatings and inks (Kroeze, 1995; U.S. EPA, 1992a). [Update/Elaboration] Note that although the use of PFCs for plasma etching is mentioned as an example in footnotes 2 and 3 to this table, the methodology for estimating emissions is described in Chapter 6 of Volume 3: Electronics Industry Emissions.							
<sup>3</sup> PFC-14 (chemically CF <sub>4</sub> ) is used as a minor component of a proprietary blend. Its main use is for semiconductor etching.							
<sup>4</sup> PFC-51-14 is an inert material, which has little or nil ability to dissolve soils. It can be used as a carrier for other solvents or to dissolve and deposit disk drive lubricants. PFCs are also used to test that sealed components are hermetically sealed.							

<sup>3</sup> Refer to <http://hq.unep.org/ozone/> for the phaseout schedules dictated under the Montreal Protocol.

Second-order Draft

## 7.1.2 General methodological issues for all ODS substitute applications

### 7.1.2.1 OVERVIEW OF ODS SUBSTITUTE ISSUES

No refinement

### 7.1.2.2 CHOICE OF METHOD

#### TIER 1 METHODS

No refinement

##### Tier 1a – Emission-factor approach at the application level

No refinement

##### Tier 1b – Mass-balance approach at the application level

No refinement

#### TIER 2 METHODS – APPLIED AT THE SUB-APPLICATION LEVEL

There are two versions of the Tier 2 method, both of which result in emission calculations for each individual chemical and distinct types of products or equipment at the sub-application level or within a sub-application. The individual chemicals and products/equipment within the sub-application form the matrix referred to earlier in this section and their analysis is comparable with methods currently applied by the Alternative Fluorocarbons Environmental Acceptability Study (AFEAS) for CFCs, HCFCs and HFCs (McCulloch, Midgley and Ashford, 2001 and 2003; Ashford, Clodic, Kuijpers and McCulloch, 2004).

Both versions of the Tier 2 methodology follow two general steps:

- i. Calculation or estimation of the time series of net consumption of each individual HFC and PFC chemical at a relatively detailed product and equipment level to establish the consumption basis for emission calculations. (e.g., refrigerators, other stationary refrigeration/AC equipment, appliance foams, insulated panels, pipe insulation, etc.)
- ii. Estimation of emissions using the activity data and resulting bank calculations derived from step (i), and either emission factors that reflect the unique emission characteristics related to various processes, products and equipment (Tier 2a) or, relevant new and retiring equipment information at the sub-application level to support a mass balance approach. (Tier 2b).

The difference between Tier 2a and Tier 2b is the same as that for Tier 1a and Tier 1b – namely Tier 2a methods use an emission-factor approach while Tier 2b methods follow a mass-balance approach. Both, however, need to be operated at a level of disaggregation appropriate to a Tier 2 method, typically at least at the sub-application level.

If the requisite data are available, a Tier 2 method is preferred for estimating emissions from ODS substitutes, particularly where the sub-applications within an overall application area are relatively heterogeneous. Some countries may already have the relevant information available to apply a Tier 2 methodology. Other countries might not have access to data for Tier 2 at present, but they are encouraged to establish routines to collect either country-specific or globally or regionally-derived activity data by chemical and sub-application within an application area (e.g., different types of refrigeration and air conditioning sub-applications). Tier 1, in contrast, requires data collection at a more aggregated application level (e.g., refrigeration and air conditioning in its totality).

As a first step in using the Tier 2 method, countries may wish to make first order approximation of the information needed for step (i). This will give direction to more focused data collection efforts in certain application areas or sub-categories. Table 7.3 gives examples of HFC/PFC consumption distribution at the application level in 2002 among various application areas in selected countries.

[Update/Elaboration]

Table 7.3a gives the consumption distribution in 2015 for the Article 5 (developing countries) and Non-Article 5 Parties (developed countries) to the Montreal Protocol. The distribution is based on estimated consumption for HFCs in CO<sub>2</sub>-equivalents (UNEP-TEAP 2016). The most important application area by far was Refrigeration

and Air Conditioning. Table 7.3b gives the consumption of HFCs for Refrigeration and Air Conditioning in 2015 for Article 5 Parties, by substance and sub-application. Table 7.3c shows the share of total consumption used for manufacturing (filling of new equipment) and servicing (refilling of operating equipment).

TABLE 7.3 (UNCHANGED) EXAMPLE DISTRIBUTION OF HFC/PFC USE BY APPLICATION AREA (2002) <sup>a</sup>						
Country	Refrigeration Air Conditioning	Foam Blowing	Solvent <sup>b</sup>	Fire Protection <sup>b</sup>	Aerosol Propellant <sup>b</sup>	Other Applications <sup>b</sup>
Austria	18%	81%	0%	1%	0%	0%
Denmark	81%	18%	0%	0%	1%	0%
Norway	72%	11%	0%	16%	1%	0%
Sweden	48%	42%	0%	4%	6%	0%
United Kingdom	31%	22%	0%	9%	38%	0%

Source:

<sup>a</sup> UNFCCC Reported Data for 2002 as re-submitted in 2004

<sup>b</sup> A zero declaration may not always reflect non-use but could reflect reporting under other categories.

TABLE 7.3A (NEW) DISTRIBUTION OF HFC USE BY APPLICATION AREA FOR 2015 <sup>a</sup>					
COUNTRY	RAC	FOAMS	MDIs	TECH AEROSOLS	FIRE PROTECTION AND OTHERS
Article 5 Parties <sup>b</sup>	91 %	2 %	1 %	1 %	5 %
Non-Article 5 Parties <sup>c</sup>	76 %	12 %	3 %	5 %	3 %

Source:

a TEAP September 2016 Report Volume II

b Developing countries. See list of Article 5 Parties to the Montreal protocol at the Unep Ozone Secretariat web page

c Developed countries. See list of Non-Article 5 Parties to the Montreal protocol at the Unep Ozone Secretariat web page

TABLE 7.3B (NEW) HFC CONSUMPTION FOR REFRIGERATION AND AIR CONDITIONING IN ARTICLE 5 PARTIES <sup>a</sup> , PERCENT OF TOTAL BY SUBSTANCE AND SUB-APPLICATION AREA FOR 2015 <sup>b</sup>						
	Total	HFC-134a	R-410A	R-407C	R-404A	R-507
TOTAL	100	27	39	20	7	7
Stationary Air Conditioning	60	1	39	20	-	-
Mobile Air Conditioning	19	19	-	-	-	-
Commercial Refrigeration	13	2	-	-	6	6
Domestic Refrigeration	5	5	-	-	-	-
Industrial Refrigeration	2	<1	-	-	1	1
Transport Refrigeration	1	<1	-	-	<1	<1

Source:

<sup>a</sup> UNEP/OzL.Pro/ExCom/78/4

<sup>b</sup> Developing countries. See list of Article 5 Parties to the Montreal protocol at the Unep Ozone Secretariat web page



Second-order Draft

TABLE 7.3C (NEW) HFC CONSUMPTION FOR REFRIGERATION AND AIR CONDITIONING IN ARTICLE 5 PARTIES <sup>B</sup> . PER CENT OF TOTAL BY MANUFACTURING AND SERVICING FOR 2015 <sup>A</sup>	
Manufacturing	Servicing
68	32
Source: <sup>a</sup> UNEP/OzL.Pro/ExCom/78/4 <sup>b</sup> Developing countries. See list of Article 5 Parties to the Montreal protocol at the Unep Ozone Secreteriat web page	

*Good practice guidance* in this section deals with variations of the Tier 2 method. Tier 1 methods, covered previously, are generally seen as default methods where the application is not a *key category* and data availability is limited. (Exceptionally, for Fire Protection, Tier 1a method with country-specific activity data and emission factor will be used in the case it is identified as *key category*.) Each sub-section of Sections 7.2 to 7.7 discusses how to apply these methods to specific ODS applications, reviews existing data sources, and identifies gaps therein.

## **Tier 2a – Emission-factor approach**

No refinement

## **Tier 2b – Mass-balance approach**

No refinement

### **7.1.2.3 CHOICE OF EMISSION FACTORS**

No refinement

### **7.1.2.4 CHOICE OF ACTIVITY DATA**

No refinement

### **7.1.2.5 COMPLETENESS**

No refinement

### **7.1.2.6 DEVELOPING A CONSISTENT TIME SERIES**

No refinement

## **7.1.3 Uncertainty assessment**

No refinement

## **7.1.4 Quality Assurance/Quality Control (QA/QC), Reporting and Documentation for all ODS substitutes applications**

No refinement

## **7.2 SOLVENTS (NON-AEROSOL)**

No refinement

## **7.3 AEROSOLS (PROPELLANTS AND SOLVENTS)**

No Refinement

## **7.4 FOAM BLOWING AGENTS**

No refinement

## 7.5 REFRIGERATION AND AIR CONDITIONING

### 7.5.1 Chemicals covered in this application area

No refinement

### 7.5.2 Methodological issues

#### 7.5.2.1 CHOICE OF METHOD

##### TIER 1

##### Tier 1 a/b

No refinement

##### TIER 2

##### Overview

No refinement

##### Tier 2b - Mass-balance approach

No refinement

##### Tier 2a - Emission-factor approach

No refinement

##### *Refrigerant management of containers*

No refinement

##### *Refrigerant charge emissions of new equipment*

No refinement

##### *Emissions during lifetime (operation and servicing)*

No refinement

##### *Emissions at end-of-life*

No refinement

[New – Box 7.2a, Box 7.2b and Box 7.2c]

## BOX 7.2A (NEW)

### HOW TO BUILD A RAC INVENTORY IN A FEW SIMPLE STEPS - TIER 1 AND 2 EMISSION FACTOR APPROACHES

#### TIER 1a/b

##### Consumption Data

Collect the data required as inputs to the calculations:

- Consumption of specific HFCs or other fluorinated substitutes for ozone depleting substances, at least in the year to be reported
- Year of introduction of the refrigerant
- Growth rate in sales of new equipment

Look for data in Refrigerant Management Plans (RMPs), HCFC Phase-out Management Plans (HPMPs) or data reported under the Montreal Protocol. To get an idea of the most important gas types and application areas, see Tables 7.3a, 7.3b and 7.3c in this update.

##### Emission Factors

Identify and apply the appropriate emission factors. The basic calculation tool contains the default tier 1 emission factor as given in the IPCC 2006 Guidelines. The reasoning behind it can be found in each subsection in the Guidelines. Adapt the default emission factors to country-specific conditions if information on these conditions is available.

##### The IPCC basic Calculation Tool

Download the basic calculation tool in the form of MS Excel worksheet “Calculation Example for 2F1” at the IPCC web site (<https://www.ipcc-nggip.iges.or.jp/public/2006gl/vol3.html>).

Tip! The “Fact sheets on HFCs” provided at the UNEP Ozone Secretariat web site (<http://ozone.unep.org/en/hfc-management-documents-2014-onwards>), particularly the overview of HFC market sectors, is a good starting point for learning about the use of fluorinated substitutes for ozone depleting substances.

#### TIER 2a

Where refrigeration and air conditioning is a key category, a Tier 2 approach should be used to estimate emissions. Building a good quality Tier 2 inventory for refrigerants is demanding, so setting up a plan for gradual improvement over time is recommended.

##### Activity data

For the Tier 2 approach, total annual emissions stem from four sources: management of refrigerant containers, refrigerant charge, banks of refrigerants and at system disposal. For the three latter sources, HFC consumption needs to be collected or estimated for each of the six sub-applications listed in Section 7.5.1 in Volume 3 of the *2006 IPCC Guidelines*.

How to estimate banked refrigerants is further discussed in Box 7.2b and Box 7.2c in this update.

Important data sources are described in Box 7.3a in this update.

##### Emission factors

Table 7.9 in Volume 3 of the *2006 IPCC Guidelines* provides ranges of default factors for the sub-applications if country-specific factors are not available.

Choose from the ranges according to country-specific conditions and document the reasons for the choices. In general, the emission factors in the low end of the ranges apply for those countries that have a voluntary or mandatory system in place to limit emissions during equipment service, use, and disposal.


##### Calculations

The IPCC basic Calculation Tool can be modified and used for Tier 2 calculations. Most countries have however built their own models adapted to the data they have available.

**BOX 7.2B (NEW)**  
**OVERVIEW OF THE BASIC ELEMENTS OF THE RAC REFRIGERANT BANK**

The emission inventory is a product of several components, reaching back to the introduction of the ODS-substitutes. In order to develop a consistent time series, inventory compilers should estimate the yearly fluxes of substances from the refrigerant *bank* (see example below).

**Schematic example of the yearly inventory development**



**Remarks to example**

- This schematic example illustrates a market with an annual increase in sales of new equipment.
- Annual consumption of refrigerant equals the quantity of new chemical used to fill new equipment as well as to refill equipment during servicing.
- Annual bank equals the bank remaining from the previous year (after accounting for emissions and any equipment refills and/or retirements) plus the charge of new equipment.
- When the level of refrigerant in equipment reaches below a certain threshold (depending on the type of equipment), refill servicing is needed to maintain cooling function.
- In this schematic, X is equated to the lifetime of the equipment. Thus, the equipment installed in Year 0 is retired in Year X.
- This schematic example does not cover emissions from management of containers.

**Estimation of annual refrigerant bank**

$$Bank_y = Bank_{y-1} + Addition_y - Removal_y$$

Where:

$Bank_y$  = Annual refrigerant bank beginning of year y, kg

$Bank_{y-1}$  = Annual refrigerant bank end of year y-1, kg

$Addition_y$  = Addition of new substances year y, kg

$Removal_y$  = Removal of substances exported, emitted or destroyed year y, kg

**1. The starting point: Bank of ODS-substitutes in operating equipment**

The starting point for the annual estimates is always a snapshot of the bank of ODS-substitutes at the end of the previous year. For each of the relevant RAC sub-applications (see table 7.9), you need to have an estimate of the types and amounts of ODS-substitute it contains. Note that in a given year, RAC equipment in a sub-application may contain several different types of chemicals. If this is the case, you need to estimate the share of HFCs in relation to other substances (e.g. HCFC, NH<sub>3</sub>, etc.).

In the future, this kind of snapshot of the equipment population (bank) will be one of the outputs from the calculation model you run every year. In the first year of making the inventory, however, you will have to start from scratch and spend time putting together information on what the bank looks like in your country. How to do this is described in box 7.2C.

**2. Annual addition of new substances**

For each of the RAC sub-applications, you then need to add the amount of ODS-substitutes being put on the market during the year for which you are making an inventory.

A common approach for estimating the additions to the bank in a certain year is to use figures on domestic sales of ODS-substitutes. The sum of production and imports, minus exports, is normally the basis for estimating domestic sales. For instance, if your country is producing neither HFC-134a nor cars, the annual addition to the bank of HFC-134a in mobile air conditioning will consist of the HFC-134a contained in imported cars plus the HFC-134a imported in bulk (i.e., in containers, either large or small) for refilling of air conditioning in cars that are in use.

It is necessary to keep track of the sales of chemicals both in bulk and in equipment. These figures are both needed for keeping track of the structure of the bank and estimating emissions.

**Bulk data:** Only a few countries produce ODS-substitutes; hence most compilers solely need to focus on the imported amounts. Ideally, you want to know the amount of each kind of ODS-substitute imported to your country, and what it will be used for; whether it will be used for manufacturing/assembly (filling of new equipment) or for servicing of equipment in use (refilling), and the kind of sub-application it is used for.

See box 7.3a for tips on where to find this kind of data.

**Data on equipment:** Commonly, you will have to obtain figures on the number of equipment units, and combine it with information on type and content of ODS-substitute.

See box 7.3a for tips on where to find this kind of data.

**3. Removal of substances exported, emitted or destroyed**

From the annual bank you should subtract the amounts of ODS-substitutes exported in bulk or in products; emitted during filling of new equipment, due to annual leakage, during service, or at end-of-life treatment; or leaving the bank due to incineration/destruction. Any amount of chemicals recovered and recycled should not be deducted from the bank.

**Export:** Exports of chemicals in bulk may occur, but are normally not significant for other than the producing countries. For countries producing RAC equipment, export of chemicals in products may be significant and the amounts of ODS-substitutes exported should be deducted from the annual sales.

## Second-order Draft

**Emissions:** Emissions from filling of new equipment include emissions at manufacturing and at assembly. Annual lifetime emissions include annual leakage from the bank and emissions during intermittent servicing (not relevant for all sub-applications). Emissions from end-of-life treatment equal the amounts remaining in retired RAC equipment minus the fractions recovered and recycled or destroyed. In cases where destruction of chemicals occurs, there may be emissions released during the incineration process.

**Retired equipment:** In order to know when a group of RAC equipment is retired, you need to sort and track the equipment by age in your model. Then you will have information on the number of years a certain group of equipment has been in the bank. When this group of equipment reaches its assumed end of life, the amount of refrigerant remaining in the group will either be released as emissions (leaving the bank) or recovered and reused (moving to new or existing equipment but remaining in the bank). For RAC equipment where no service is expected during its lifetime, refrigerants remaining at end-of-life equals initial charge minus lifetime emission factor times equipment lifetime.

**Destruction:** Currently quite small on a global scale, but may be relevant in countries with measures in place. In some countries, recovered ODS-substitutes may be exported to other countries for destruction.

#### **4. The result: New bank of ODS-substitutes in operating equipment**

The result is the new bank at the end of the current year. This is the starting point for next year's emission estimates.

**BOX 7.2C (NEW)**  
**HOW TO BUILD THE BANK OF ODS-SUBSTITUTES IN RAC**

**How to map the contents and structure of the bank:**

There are two common ways of “knowing” what the bank currently looks like:

- **Building it through annual data on fluxes, starting at year 0.**

If data on domestic sales for all years since the ODS-substitutes were first introduced is available, this can be used to move forward from zero to the current bank by adding the sales and subtracting the emissions every year (see box 7.2). (Note that any refrigerant recovered from retiring equipment and used to fill new equipment or to refill existing equipment remains part of the bank.)

- **Counting the number of equipment units currently in place.**

Most countries setting up an inventory for the first time do not have information on the flux of ODS-substitutes for all years back to when the substitution first started. An alternative way of estimating the contents and structure of the bank is to start by estimating the number of equipment units in the country. This number can then be combined with information on the types of ODS-substitutes normally used and the average amount in each unit to build the bank.

For instance, the numbers of some kinds of equipment, like cars, might be available from national statistics or from a national register used for taxation. Industrial organizations often have statistics on mass-produced types of equipment, like numbers of household refrigerators, small air conditioning units, heat pumps and cars. If not, they might help you to estimate the sizes of markets, and hence consumption.

It is often challenging to get information on the number of large refrigeration and air conditioning systems. You might need to estimate this using information on the number of, for instance, large office buildings, hospitals, universities etc. in your country. Then you need to combine this with information on the typical number and types of air conditioning units per building. Again, industrial associations can often be helpful in getting this sort of information.

**How to get all the needed information back to year 0:**

Most countries need to create time series back to “year 0” when the ODS-substitutes were first introduced in the relevant country. If the current bank was built on the basis of annual data on fluxes, as described above, then all needed information is already there.

If not, a common way of handling this is to interpolate (fill in the holes in the time series) between the year of a chemical’s introduction and the current situation (bank), either linearly or by some proxy data, like growth in sales of equipment.

First, gather information on the year each relevant kind of ODS-substitute was first used in each relevant type of equipment (sub-application) in your country (for instance, the year HFC-134a was first used in mobile air conditioning in your country). If this information is not available, you can make reasonable assumptions based on, for example, the ODS phase-out schedule in your country and/or substitution patterns in countries similar to yours.

Then, choose a method to fill in the years between year 0 and the current year. If you have no information on the development of the bank, a simple linear interpolation should be used. Otherwise, if some kind of information on the development is available, like the annual growth in sales of cars with air conditioning, this data can be used to model the bank year by year. See the excel workbook “Calculation Example for 2F1” provided in the *2006 IPCC Guidelines* for example on how to back-calculate both the bank and the emissions using this simplified approach.

See box 7.3a for tips on where to find data.



## 7.5.2.2 CHOICE OF EMISSION FACTORS

### Tier 1a/b method

As explained within Section 7.5.2.1, Choice of Method, a composite emission factor is required to complete a Tier 1 method. Since the sub-applications within the refrigeration and air conditioning application are relatively heterogeneous, the validity of any single composite emission factor must be in doubt unless it takes into consideration the particular mix of sub-applications in the country. It is therefore *good practice* to develop composite emission factors on the basis of research within the country. The over-arching default emissions factor of 15 percent of the bank annually is used in the example of spreadsheet calculation contained in the 2006 *Guidelines* CDROM attached to these *Guidelines*.

### Tier 2a method

[Update/Elaboration]

*Good practice* for choosing emission factors is to use country-specific data, based on information provided by equipment manufacturers, service providers, disposal companies, and independent studies. When national data are unavailable, inventory compilers should use the default emission factors shown in Table 7.9, Estimates for Charge, Lifetime and Emission Factors, which summarises best estimates of equipment charge, lifetime, emission factors during useful life, and parameters for end-of-life emissions. If data used to calculate the refrigerant bank cannot be broken down into the sub-applications as in Table 7.9, it is *good practice* to divide the bank by type of equipment using expert judgement, and calculate composite emission factors weighted according to that relative share, as proposed for Tier 1a/b. The default values in Table 7.9 reflect the current state of knowledge about the industry, and are provided as ranges rather than point estimates. Inventory compilers should choose from the range according to country-specific conditions, and document the reasons for their choices. The lower end of the lifetime and emission factor ranges is intended to indicate the status within developed countries, while the upper end of each range is intended to indicate the status within developing countries. Emission factors in the low end of the ranges should especially apply for those countries that have a mandatory or voluntary system in place to limit emissions during equipment service, use, and disposal.

Studies of emission rates in Japan for 2009 (Japan Refrigeration and Air Conditioning Industry Association, 2009) and Germany for 2011-2015 (Umweltbundesamt, 2015) showed that the average emission factors in these countries were close to the lower range for most sub-application categories within the application area of Stationary Refrigeration and Air Conditioning. For the sub-application areas Medium and Large Commercial Refrigeration and Industrial Refrigeration, the German study provided leakage rates below the ranges given in Table 7.9. These factors are given in Table 7.9a and are intended to serve as examples of emission rates for highly maintained systems. Only countries with similar systems and regulations or incentives in place should consider using these factors for relevant years.

It is *good practice* to consider applying different emission factors in different years to reflect improvements in service and disposal practices and in equipment design and materials. All of these can reduce emission rates. Changes in emission factors over time could also be appropriate for countries that have introduced mandatory periodical inspection and repair regulations/schemes or similar incentives.

For mobile air conditioning, emissions can occur during different stages of the useful equipment life: regular leaks (e.g. from seals), irregular leaks (e.g. due to accidents) and at service (maintenance and refilling). The 2006 *IPCC Guidelines* default ranges in Table 7.9 encompass emissions from all stages. Several newer studies (e.g. Schwarz and Harnisch (2003), Japan Automobile Manufacturers Association (2008), Papasavva *et al.* (2009), Clodic *et al.* (2011), Kim and Kim (2014), and Minnesota Pollution Control Agency (2017)) indicate that annual emission rates for modern passenger cars may be lower than the default lifetime emission factor lower range. However, in most cases the presented emission rates include only regular leaks, or regular and irregular leaks. It is *good practice* to include emissions from all three stages when choosing lifetime emission factors. As the practice for mobile A/C services may vary considerably between countries and over time, inventory compilers should investigate the national circumstances when developing country-specific emission factors. In some countries A/C RRR service units (recover/recycle/recharge) are used to significantly reduce emissions at the service stage.

There are few studies on remaining charge of refrigerants at end-of-life ( $p$ ) and recovery efficiency ( $n_{rec}$ ) in MAC (e.g. Kim and Kim (2014), Wimberger (2010), and Schwarz (2012)). Emissions at end-of-life depend on national practices and regulations. Some countries have started mandatory recovery of refrigerants at the end-of-life, in which case the recovery efficiency could be higher than the suggested ranges in Table 7.9. Inventory compilers should therefore investigate the national conditions when developing country-specific factors for recovery efficiency ( $n_{rec}$ ).

Some import and export of used vehicles and end-of-life vehicles occurs between countries (mostly from developed countries to developing countries). It is important for inventory compilers to take into account such

flows of MAC equipment when estimating emissions from MAC as it may affect the composition of vehicle stock at various emission stages (lifetime and end-of-life).

[Update/Elaboration – Table 7.9]

TABLE 7.9 (UPDATED)						
DEFAULT ESTIMATES <sup>1</sup> FOR CHARGE, LIFETIME AND EMISSION FACTORS FOR REFRIGERATION AND AIR-CONDITIONING SYSTEMS						
Sub-application	Charge (kg)	Lifetimes (years) <sup>2</sup>	Emission Factors (% of initial charge/year) <sup>3</sup>		End-of-Life Emission (%)	
Factor in Equation	(M)	(d)	(k)	(x)	( $\eta_{rec,d}$ )	(p)
			Charge	Lifetime	Recovery Efficiency <sup>4</sup>	Initial Charge Remaining
Domestic Refrigeration	$0.05 \leq M \leq 0.5$	$12 \leq d \leq 20$	$0.2 \leq k \leq 1$	$0.1 \leq x \leq 0.5$	$0 < \eta_{rec,d} < 70$	$0 < p < 80$
Stand-alone Commercial Applications	$0.2 \leq M \leq 6$	$10 \leq d \leq 15$	$0.5 \leq k \leq 3$	$1 \leq x \leq 15$	$0 < \eta_{rec,d} < 70$	$0 < p < 80$
Medium & Large Commercial Refrigeration	$50 \leq M \leq 2000$	$7 \leq d \leq 15$	$0.5 \leq k \leq 3$	$10 \leq x \leq 35$	$0 < \eta_{rec,d} < 70$	$50 < p < 100$
Transport Refrigeration	$3 \leq M \leq 8$	$6 \leq d \leq 9$	$0.2 \leq k \leq 1$	$15 \leq x \leq 50$	$0 < \eta_{rec,d} < 70$	$0 < p < 50$
Industrial Refrigeration including Food Processing and Cold Storage	$10 \leq M \leq 10,000$	$15 \leq d \leq 30$	$0.5 \leq k \leq 3$	$7 \leq x \leq 25$	$0 < \eta_{rec,d} < 90$	$50 < p < 100$
Chillers	$10 \leq M \leq 2000$	$15 \leq d \leq 30$	$0.2 \leq k \leq 1$	$2 \leq x \leq 15$	$0 < \eta_{rec,d} < 95$	$80 < p < 100$
Residential and Commercial A/C, including Heat Pumps	$0.5 \leq M \leq 100$	$10 \leq d \leq 20$	$0.2 \leq k \leq 1$	$1 \leq x \leq 10$	$0 < \eta_{rec,d} < 80$	$0 < p < 80$
Mobile A/C	$5 \leq M \leq 6500$ (maritime) $10 \leq M \leq 30$ (railway) $4 \leq M \leq 18$ (busses) $0.5 \leq M \leq 2$ (other MAC)	$9 \leq d \leq 16$	$0.2 \leq k \leq 0.5$	$20 \leq x \leq 40$ (maritime) $5 \leq x \leq 20$ (railway) $10^5 \leq x \leq 20$ (other MAC)	$0 < \eta_{rec,d} < 50$	$0 < p < 50$
Source:						
<sup>1</sup> Based on information contained in UNEP RTOC Reports (UNEP-RTOC, 1999; UNEP-RTOC, 2003), Schwarz and Rhiemeier (2007), Japan Refrigeration and Air Conditioning Industry Association (2009), Gallagher et al (2014), Umweltbundesamt (2015).						
<sup>2,3</sup> Lower value for developed countries and higher value for developing countries						
<sup>4</sup> The lower threshold (0%) highlights that there is no recovery in some countries.						
<sup>5</sup> Lifetime emissions down to 6 % of initial charge/year can be used for the most modern passenger car A/C for initial years in use in countries ensuring high technical level of maintenance at AC service (e.g. by the use of RRR service units). Note that generally there is a degradation of the A/C system leak tightness along its lifetime which should be taken into account in the lifetime emission factor over time.						

Second-order Draft

<b>TABLE 7. 9A (NEW)</b> <b>GERMAN STUDY 2015: EMISSION FACTORS FOR REFRIGERATION AND AIR-CONDITIONING SYSTEMS</b>	
<b>Sub-application</b>	<b>Emission Factors (% of initial charge/year)</b>
<b>Factor in Equation</b>	<b>(x)</b>
	<b>Lifetime Emission<sup>1</sup></b>
Medium & Large Commercial Refrigeration (centralized)	7.64 – 10.02
Small Commercial Refrigeration (condensing units)	3.09 -5.18
Industrial Refrigeration including Food Processing and Cold Storage	4.71
AC Chiller	3.39
AC Multisplit/VRF	3.80
Source: Umweltbundesamt (2015) <sup>1</sup> These emission factors are intended to serve as examples of emission rates for highly maintained systems. Only countries with similar systems and regulations or incentives in place should consider using these factors for relevant years	

### 7.5.2.3 CHOICE OF ACTIVITY DATA

#### Tier 1a/b method

No refinement

#### Tier 2 methods

No refinement

#### Other shared issues

No refinement

**BOX 7.3 (UNCHANGED)**  
**ACCOUNTING FOR IMPORTS AND EXPORTS OF REFRIGERANT AND EQUIPMENT**  
 No refinement

[New – Box 7.3A, see below]

**BOX 7.3A (NEW)**

**COMMON DATA SOURCES FOR THE ODS-SUBSTITUTES INVENTORY**

This box provides a short description of common data sources for the ODS-substitutes inventory, complementing table 7.10 in the *2006 IPCC Guidelines*. Examples of data are production, imports, exports and destruction of ODS-substitutes and equipment containing ODS-substitutes. Number of equipment units and growth rates in sales are also data commonly collected.

**Governmental reports**

Most countries have collected data for Refrigerant Management Plans (RMPs) or HCFC Phase-out Management Plans (HPMPs) through ODS-alternatives surveys, and some countries have begun monitoring HFC consumption due to the inclusion of HFCs in the Montreal protocol. Countries that have ratified the Kigali amendment to the Montreal Protocol will have to report consumption data on HFCs annually.

The consumption data generally contain information on:

- past consumption of CFCs, current and past consumption of HCFCs and possibly also HFCs. Data on ODS are often given in ODP tonnes, which can be converted into metric tonnes using the substance-specific ODP values;
- sector specific consumption of HCFCs and possibly also HFCs (e.g. amounts used in air conditioning, refrigeration, fire extinguishers, aerosols etc.);
- breakdown of HCFCs according to their use at each lifecycle stage such as manufacturing/assembly (initial charge) or servicing (refill);

**Surveys**

There is often a limited number of companies producing, importing and exporting refrigerants (ODS-substitutes) in bulk; hence a way to obtain high quality data is to ask the producers, importers, and exporters for information. They should provide information on the amount of gas produced, imported, or exported in a certain year and what equipment type it will be used in if these data are available.

The number of companies importing equipment containing ODS-substitutes can be large, and surveying this might be resource intensive. If this is the case, other data sources such as sales statistics or national customs registers (see below) may be used instead.

Surveys can also be a way to obtain information on ODS substitutes from end-users. Generally, this requires good knowledge of the market and preparatory market research may be needed before launching a survey.

Surveys can also be a way to discover areas and applications previously unknown to the inventory compilers.

**National Customs Registers**

National Customs Registers contain information on imports and exports of chemicals and equipment potentially containing ODS-substitutes. If the ODS-substitutes are subject to tax, such a register might provide the amounts of refrigerant contained in the products. If not, you will probably need to apply assumptions on types of ODS-substitute and average charge sizes on number of equipment units.

**Other national registers**

Many countries have national registers of cars uses for taxation purposes. This data source might provide figures on the number of cars, and possibly other information like age and size.

National Product Register/European Chemical Agency: In some countries, a national Products Register is used to store information on chemical products (ODS-substitutes) that are manufactured in or transferred or imported into the country and information on the ways in which these are being used.

**Industrial organizations**

Industrial organizations or trade associations often have statistics on mass-produced types of equipment, like numbers of household refrigerators, small air conditioning units, heat pumps and cars.

## Second-order Draft

If not, they might help with assessments of the size of markets, and hence the consumption figures. It is often challenging to get information on the number of large refrigeration and air conditioning systems. Industrial organizations might provide useful information like annual growth in sales of equipment and average charge size of various types of equipment.

#### National statistics

Many countries have national offices publishing annual statistics with useful information, like the stock of vehicles and buildings (number or area by type of building), or production of commodities.

### 7.5.2.4 APPLYING TIER 2 METHODS – THE EXAMPLE OF MOBILE AIR CONDITIONING (MAC)

The Box 7.4 below sets out the step-by-step approach required to assess the emissions from the mobile air conditioning sub-application of a hypothetical country's inventory. The method adopted is primarily a Tier 2a approach, although there are also elements which would be equally applicable to Tier 2b. This example, therefore, highlights the reality that pure approaches and methods are rare in practice. There will often be a mix of emission-factor approach and mass-balance approach as well as a mix of country-specific data and globally or regionally derived data. As pointed out in Section 7.1.2.1, one method, approach or dataset will often be used to cross-check another. This example also demonstrates that a detailed implementation of the Tier 2a method requires a significant amount information gathering about a sub-application. Once established, it is less burdensome to implement the approach in subsequent years. Also note that assumptions made are for example only; inventory compilers should collect country-specific information rather than using the assumptions shown.

[Update- Box 7.4]

#### Box 7.4 (UPDATED)

##### EXAMPLE OF THE APPLICATION OF A TIER 2A CALCULATION FOR MOBILE AIR CONDITIONING

#### Introduction

National inventories and other studies to date show that emissions of HFC-134a from mobile air conditioners (MACs) contribute significantly to the Refrigeration and Air Conditioning (RAC) Application emissions and the ODS Substitutes Category emissions. For many countries, emissions from MACs will comprise 50 percent or more of the RAC emissions and possibly more than 50 percent of the total ODS Substitutes Category emissions. This is due to many factors, including:

- The phaseout of ODSs to HFCs in MACs occurred earlier and more quickly than other Sub-Applications, such as residential (stationary) air conditioning and commercial refrigeration (supermarkets), which still rely substantially on ODSs.
- MACs are subject to extremes in terms of physical shock and vibration and hence emissions tend to be large.
- The lifetime of MACs tends to be shorter than many other RAC Sub-Applications, so that end-of-life emissions are seen earlier and equipment stocks relying on ODSs are replaced sooner with HFCs.
- Due to the small charge of refrigerant involved, recovery from MACs is often seen as uneconomical and hence is not often practiced during service and disposal.

In addition, data on vehicle purchases and registrations in a country are often known to a higher degree of quality or are easily obtained. Hence, it is *good practice* to estimate emissions from this Sub-Application. The following text describes how the general equations for the RAC Application can be applied to the MAC Sub-Application.

#### Data Gathering and Assumptions

An accurate estimate of MAC emissions may be obtained by collecting some data at the Sub-Application level and applying a few basic assumptions to simplify the data and calculations required, as follows:

*Refrigerant Type.* It will be important to separate each data point by refrigerant, so that emissions of each refrigerant are calculated separately. For MACs, this may be simplified by the fact that all

MACs produced since the mid- to late-1990s use HFC-134a as the refrigerant. However, CFC-12 was used in the past and still exists in some operating systems. Furthermore, for the future other refrigerants such as HFC-152a and R-744 (carbon dioxide) are being considered.

*Refrigerant Sold in Containers ( $RM_t$ )*. For MACs, refrigerant generally comes in three basic types of containers – ‘bulk containers’ sent to vehicle manufacturers to fill new MACs, ‘small cans’ containing about 300-500 grams of refrigerant generally used by individuals servicing their own equipment, and ‘cylinders’ containing about 10-15 kilograms of refrigerant used by shops that service many vehicles. If one assumes no losses from bulk containers (see below), then in order to calculate  $E_{\text{containers}}$ , one needs to know the total refrigerant sold in small cans ( $RM_{sc}$ ) and cylinders ( $RM_{cy}$ ). It will be important to distinguish the refrigerant sold into different Sub-Applications (e.g., HFC-134a is also used in the chillers and domestic refrigeration Sub-Applications) so that only the refrigerant sold for MACs is used in the calculations. This data may be obtained from small can packagers and refrigerant producers/distributors.

*Container Heels ( $c$ )*. For this example, we assume the heels from service containers are not recovered (e.g., the cylinders are discarded, not reused) and are  $c_{sc} = 20\%$  for the small can and  $c_{cy} = 2\%$  for the cylinder. Because bulk refrigerant containers generally go back to the refrigerant producer and are refilled, we can assume there are no heels that would be emitted and hence  $c_{\text{bulk}} = 0\%$ .

*MACs Produced Each Year ( $N_t$ )*. If the number of MACs placed in service each year is not known, an estimate can be made by multiplying the number of cars placed in service each year by an estimate of the percentage that were sold with MACs. These data may be available from automobile manufacturers, MAC producers/suppliers, or government agencies involved in transportation, infrastructure and highway safety. If more than one type of refrigerant is used, it is important to separate each  $N_t$  into the different refrigerants, e.g.,  $N_{1994} = N_{1994,\text{CFC-12}} + N_{1994,\text{HFC-134a}}$ .

*Nominal Charge of Each MAC ( $m_t$ )*. This factor would likely vary by the type of vehicle; for instance small passenger cars will likely have lower refrigerant charges than buses or larger cars, especially those with multiple evaporators. Likewise, this could vary over time, for instance decreasing as manufacturers make smaller systems for the same vehicle size, or increasing as larger cars and more multiple-evaporator units enter the market. For this example, we assume a constant over time at an average  $m = 0.7$  kg, which is typical of small to medium-sized passenger cars.

*Refrigerant Charged into New Equipment ( $M_t$ )*. This is easily calculated as  $M_t = N_t \cdot m_t = 0.7 \cdot N_t$ .

*Assembly Losses ( $k$ )*. This is used to calculate the Charge Emissions, also referred to as ‘First-Fill Emissions.’ The loss rate is often small, on the order of  $k = 0.5\%$  or smaller. For simplicity, we assume  $k = 0$  in this example.

*Lifetime ( $d$ )*. The presumed lifetime of a MAC. This variable can be based on national data and can be different for different types of MACs (passenger cars, buses, etc.) For this example, we assume the lifetime of all MACs is  $d = 12$  years.

*Bank in Existing Equipment ( $B$ )*. The bank will be the amount of refrigerant in MACs put into service, minus the amount of refrigerant in MACs disposed, plus the amount of refrigerant used to service MACs, minus the amount that has leaked. In actuality, a given MAC will probably leak over several years before being serviced. Rather than attempting to account for this, for this example we apply Equation 7.13 which assumes all MACs are serviced each year such that the estimated charge of each MAC is the same as the nominal charge. The annual emission rate is averaged to account for this assumption. This will only produce small errors unless the year-to-year sales of MACs fluctuate widely. Hence the bank in any given year is the sum of the Refrigerant Charged into New Equipment each year from the current year back to the assumed average lifetime of the equipment. Thus,

$$B_t = \sum_{i=1}^d M_{t-i+1}$$

For example, using  $d = 12$  years, the bank in 2006 would be  $B_{2006} = M_{2006} + M_{2005} + M_{2004} + \dots + M_{1997} + M_{1996} + M_{1995}$ .

*Annual Emission Rate ( $x$ )*. This factor accounts for both leaks from equipment as well as any emissions during service. Both of these items can be different for different types of MACs and can

## Second-order Draft

also vary by when the MAC was produced (i.e., older MACs may leak more than newer MACs). If annual servicing does not occur, the amount emitted at any servicing event needs to be average over the number of years between servicing event to obtain the annual rate. This amount is likely to vary considerably depending on national conditions and what type(s) of service is (are) performed. Whether recovery of the given charge before service is performed must be considered, and may be deducted in part by examining the amount of refrigerant sold in small cans versus cylinders. For this example, we assume that 15% of the nominal charge is leaked each year and 5% on average is emitted during servicing. Hence,  $x = 20\%$ .

*Residual Charge in MACs Disposed ( $p$ )*. Assuming that the MAC is serviced the year before it is disposed, and that the annual emission rate is estimated, this is easily calculated as  $p = 1 - x$ . In our example,  $p = 1 - 15\% = 0.85$ .

*Recovery Efficiency ( $n_{rec}$ )*. If no regulations or incentives exist to require recovery of refrigerant from MACs disposed, then likely very little will occur. So, for this example, we assume that  $n_{rec} = 0$ .

### Calculation of Different Types of Emissions

Now that these data have been gathered and assumptions have been made, calculating the emissions may be performed. An example for year  $t = 2006$  follows:

*Container Emissions (Equation 7.11).*

$$E_{containers,2006} = RM_{cy,2006} \cdot c_{cy} + RM_{sc,2006} \cdot c_{sc} = 0.02 \cdot RM_{cy,2006} + 0.2 \cdot RM_{sc,2006}$$

*Charging Emissions (Equation 7.11).*

$$E_{charge,2006} = M_{2006} \cdot k = 0$$

*Lifetime (Operating and Servicing) Emissions (Equation 7.13).*

$$\begin{aligned} E_{operation,2006} &= B_{2006} \cdot x = 0.20 \cdot B_{2006} = 0.20 \cdot \sum_{i=1}^d M_{t-i+1} \\ &= 0.20 \cdot (M_{2006} + M_{2005} + M_{2004} + \dots + M_{1997} + M_{1996} + M_{1995}) \\ &= 0.20 \cdot m \cdot (N_{2006} + N_{2005} + N_{2004} + \dots + N_{1997} + N_{1996} + N_{1995}) \\ &= 0.20 \cdot 0.7 \cdot (N_{2006} + N_{2005} + N_{2004} + \dots + N_{1997} + N_{1996} + N_{1995}) \\ &= 0.14 \cdot (N_{2006} + N_{2005} + N_{2004} + \dots + N_{1997} + N_{1996} + N_{1995}) \end{aligned}$$

*End-of-Life Emissions (Equation 7.14).*

$$\begin{aligned} E_{end-of-life,2006} &= M_{2006-d} \cdot p \cdot (1 - n_{rec}) = M_{2006-12} \cdot 0.85 \cdot (1 - 0) \\ &= 0.85 \cdot M_{1994} = 0.85 \cdot 0.7 \cdot N_{1994} = 0.595 \cdot N_{1994} \end{aligned}$$

### Calculation of Total Emissions

*Total MAC Emissions (Equation 7.10).*

$$\begin{aligned} E_{total,2006} &= E_{containers,2006} + E_{charge,2006} + E_{lifetime,2006} + E_{servicing,2006} + E_{end-of-life,2006} \\ &= 0.02 \cdot RM_{cy,2006} + 0.2 \cdot RM_{sc,2006} + 0 \\ &\quad + 0.14 \cdot (N_{2006} + N_{2005} + N_{2004} + \dots + N_{1997} + N_{1996} + N_{1995}) + 0.595 \cdot N_{1994} \\ &= 0.02 \cdot RM_{cy,2006} + 0.2 \cdot RM_{sc,2006} \\ &\quad + 0.14 \cdot (N_{2006} + N_{2005} + N_{2004} + \dots + N_{1997} + N_{1996} + N_{1995}) + 0.595 \cdot N_{1994} \end{aligned}$$

The only unknowns are:

- $RM_{sc}$  – refrigerant (in kilograms) sold in small cans to service MACs, which may be obtained from small can packagers;
- $RM_{cy}$  – refrigerant (in kilograms) sold in cylinders to service MACs, which may be obtained from refrigerant producers/distributors; and,

- $N_t$  – the number of MACs put in service each year, which may be available from automobile manufacturers, MAC producers/suppliers, or government agencies involved in transportation, infrastructure and highway safety.

If the emissions from refrigerant containers and from end-of-life are not included, for example if it is believed that service cylinders are completely evacuated and minimal MACs reach their end-of-life in the given year, this equation becomes simply an activity (the number of MACs) multiplied by an emission factor (annual emission rate times average charge size, in this case 0.14 kg per MAC). This calculation yields the total emissions in kilograms of refrigerant. Keeping each refrigerant separate and multiplying each sum by the refrigerant's GWP will yield kilograms of CO<sub>2</sub> equivalent emissions. Dividing by 1 billion (10<sup>9</sup>) will yield emissions in teragrams of CO<sub>2</sub> equivalent (TgCO<sub>2</sub>eq).

#### 7.5.2.5 COMPLETENESS

No refinement

#### 7.5.2.6 DEVELOPING A CONSISTENT TIME SERIES

No refinement

### 7.5.3 Uncertainty assessment

No refinement

### 7.5.4 Quality Assurance/Quality Control (QA/QC), Reporting and Documentation

No refinement



Second-order Draft

776 **7.6 FIRE PROTECTION**

777 No refinement

778

779 **7.7 OTHER APPLICATIONS**

780 No refinement

781

782

## References

- Ashford, P., Clodic, D., Kuijpers, L. and McCulloch, A. (2004). Emission Profiles from the Foam and Refrigeration Sectors – Comparison with Atmospheric Concentrations, International Journal of Refrigeration, 2004.
- Ashford, P. and Jeffs, M. (2004). Development of Emissions Functions for Foams and their use in Emissions Forecasting, ETF Proceedings, April 2004.
- Clodic, D., Palandre, L., McCulloch, A., Ashford, P. and Kuijpers, L. (2004). Determination of comparative HCFC and HFC emission profiles for the Foam and Refrigeration sectors until 2015. Report for ADEME and US EPA. 2004.
- Gamlen P.H., Lane B.C., Midgley P.M. and Steed J.M (1986). The production and release to the atmosphere of CFC1<sub>3</sub> and CF<sub>2</sub>Cl<sub>2</sub> (chlorofluorocarbons CFC-11 and CFC-12). *Atmos. Environ.* 20: 1077-1085.
- IPCC (1996). Climate Change 1995: Impacts, Adaptation, and Mitigation of Climate Change: Scientific- Technical Analysis. The Contribution of Working Group II to the Second Assessment Report of the Intergovernmental Panel on Climate Change. R. T. Watson, M. C. Zinyowera, R. H. Moss, (eds.), Cambridge University Press, Cambridge.
- IPCC (1997). Revised 1996 IPCC Guidelines for National Greenhouse Inventories. Houghton J.T., Meira Filho L.G., Lim B., Tréanton K., Mamaty I., Bonduki Y., Griggs D.J. Callander B.A. (Eds). Intergovernmental Panel on Climate Change (IPCC), IPCC/OECD/IEA, Paris, France.
- IPCC (2000). Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories. Penman J., Kruger D., Galbally I., Hiraishi T., Nyenzi B., Emmanuel S., Buendia L., Hoppaus R., Martinsen T., Meijer J., Miwa K., Tanabe K. (Eds). Intergovernmental Panel on Climate Change (IPCC), IPCC/OECD/IEA/IGES, Hayama, Japan.
- IPCC (2001). Climate Change 2001: Mitigation: Contribution of Working Group III to the Third Assessment Report of the Intergovernmental Panel on Climate Change, edited by Metz, B., Davidson, O., Swart, R. and Pan, J., Cambridge University Press, Cambridge.
- IPCC/TEAP (2005). IPCC/TEAP Special Report on Safeguarding the Ozone Layer and the Global Climate System: Issues Related to Hydrofluorocarbons and Perfluorocarbons. Prepared by Working I and III of the Intergovernmental Panel on Climate Change, and the Technology and Economic Assessment Panel [Metz, B., L. Kuijpers, S. Solomon, S. O. Andersen, O. Davidson, J. Pons, D. de Jager, T. Kestin, M. Manning, and L. A. Meyer (eds.)]. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA, 488 pp.
- Kroeze, C. (1995). Fluorocarbons and SF<sub>6</sub>: Global emission inventory and control. RIVM Report No. 773001007, Bilthoven, The Netherlands.
- McCulloch A., Ashford, P. and Midgley, P.M. (2001). Historic Emissions of Fluorotrichloromethane (CFC-11) Based on a Market Survey, *Atmos. Environ.*, 35(26), 4387-4397
- McCulloch A., Midgley, P.M. and Ashford, P. (2003). Releases of Refrigerant Gases (CFC-12, HCFC-22 and HFC-134a) to the Atmosphere, *Atmos. Environ.* 37(7), 889-902
- Palandre L., Barrault, S. and Clodic, D. (2003). Inventaires et prévisions des fluides frigorigènes et de leurs émissions, France. Année 2001. Rapport pour l'ADEME, mai 2003.
- Palandre, L., Barrault, S. and Clodic, D. (2004). Inventaires et prévisions des émissions de fluides frigorigènes France - Année 2002. Rapport pour l'ADEME. Août 2004.
- Schwarz, W. and Harnisch, J. (2003). Establishing the leakage rates of Mobile Air Conditioners. Final report for the EC. Ref. B4-3040/2002/337136/MAR/C1. 17 April 2003.
- UNEP-FTOC (1999). 1998 Report of the Rigid and Flexible Foams Technical Options Committee, UNEP, Ozone Secretariat, 1999.
- UNEP-FTOC (2003). 2002 Report of the Rigid and Flexible Foams Technical Options Committee, UNEP, Ozone Secretariat, 2003.
- UNEP-HTOC (1994). Assessment Report of the Halons Technical Options Committee, Report prepared for the United Nations Environment Programme, Ozone Secretariat, Nairobi, Kenya, <http://www.ozone.org>.

## Second-order Draft

- 832 UNEP-HTOC (2003). Assessment Report of the Halons Technical Options Committee, Report for the United  
833 Nations Environment Programme, Ozone Secretariat, Nairobi, Kenya, <http://www.ozonelog.org>, 69 pp.
- 834 UNEP-RTOC (1999). 1998 Report of the Refrigeration, Air Conditioning and Heat Pumps Technical Options  
835 Committee, 1998 Assessment, UNEP, Ozone Secretariat, Nairobi, Kenya, ISBN 92-807-1731-6
- 836 UNEP-RTOC (2003). 2002 Report of the Refrigeration, air Conditioning and Heat Pumps Technical Options  
837 Committee, 2002 Assessment, UNEP, Ozone Secretariat, Nairobi, Kenya, ISBN 92-807-2288-3
- 838 UNEP-TEAP (2002). April 2002 Report of the Technology and Economic Assessment Panel, Volume 3b, Report  
839 of the Task Force on Destruction Technologies. [S. Devotta, A. Finkelstein and L. Kuijpers (ed.)]. UNEP  
840 Ozone Secretariat, Nairobi, Kenya.
- 841 UNEP-TEAP (2005). May 2005 Report of the Technology and Economic Assessment Panel, Volume 3, Report of  
842 the Task Force on Foam End-of-Life Issues, UNEP Ozone Secretariat, Nairobi, Kenya.
- 843 U.S. EPA (1992a). U.S. Environmental Protection Agency, Risk Screen on the Use of Substitutes for Class I  
844 Ozone Depleting Substances Prepared in Support of the Significant New Alternatives Policy Program  
845 (SNAP), 1992.
- 846 U.S. EPA (1992b). U.S. Environmental Protection Agency, Regulatory Impact Analysis: Compliance with Section  
847 604 of the Clean Air Act for the Phaseout of Ozone Depleting Chemicals, 1992.
- 848 U.S. EPA (2004a). U.S. Environmental Protection Agency, Analysis of International Costs to Abate HFC and PFC  
849 Emissions from Solvents (Preliminary Report), 2004
- 850 U. S. EPA (2004b). U.S. Environmental Protection Agency, The U.S. Solvent Cleaning Industry and the  
851 Transition to Non- Ozone Depleting Substances, <http://www.epa.gov/ozone/snap/solvents/index.html>
- 852 U. S. EPA/AHAM (2005). Disposal of Refrigerators/Freezers in the US – State of Practice (Baumgartner W.,  
853 Kjeldsen P. *et al.* ), 2005
- 854 Verdonik, D.P. (2004). Modelling Emissions of HFCs and PFCs in the Fire Protection Sector, Proceedings of the  
855 Earth Technology Forum, Washington, DC, 2004, 13 pp.
- 856 Verdonik, D.P. and Robin, M.L. (2004). Analysis of Emission Data, Estimates, and Modelling of Fire Protection  
857 Agents, Proceedings of the Earth Technology Forum, Washington, DC, 2004, 11 pp.
- 858 Vo and Paquet (2004). An Evaluation of Thermal Conductivity over time for Extruded Polystyrene Foams blown  
859 with HFC-134a and HCFC-142b, ETF Proceedings, April 2004
- 860
- 861 Clodic, D., Barrault, S., & Saba, S. (2010). Global inventories of the worldwide fleets of refrigerating and air-  
862 conditioning equipment in order to determine refrigerant emissions. The 1990 to 2006 updating. Mise à  
863 jour des banques, marchés et émissions de fluides frigorigènes dans la base de données RIEP au niveau  
864 mondial. ADEME/ARMINES Agreement 0874C0147– Extracts from the Final Report – April 2010
- 865 Gallagher, G., Zhan, T., Hsu, Y-K., Gupta, P., Pederson, J., Croes, B., Blake, D., Barletta, B., Meinardi, S., Ashford,  
866 P., Vetter, A., Saba, S., Slim, R., Palandre, L., Clodic, D., Mathis, P., Wagner, M., Forgie, J., Dwyer, H.,  
867 and Wolf, K. (2014). Supporting Information document for Manuscript: High-Global Warming Potential  
868 F-gas Emissions in California: Comparison of Ambient-Based versus Inventory-Based Emission Estimates,  
869 and Implications of Refined Estimates. *Environmental Science & Technology* 2014 48 (2), 1084-1093. DOI:  
870 10.1021/es403447v.
- 871 Hurwitz, M.M., Fleming, E.L., Newman, P.A., Li, F., Mlawer, E., Cady-Pereira, K. & Bailey, R. (2015). Ozone  
872 depletion by hydrofluorocarbons. *Geophys. Res. Lett.* **42**: 8686-8692.
- 873 Japan Automobile Manufacturers Association. (2008). Efforts Concerning Car Air-Conditioner Refrigerant.  
874 Materials distributed at the Global Warming Prevention Measures Subcommittee Meeting (Dec. 9, 2008),  
875 *Chemicals and Bio-industry Committee*, Industrial Structure Council
- 876 Japan Refrigeration and Air Conditioning Industry Association. (2009). Research on Japan specific emission factor  
877 of devices in operation. (Details of sample research)
- 878 Kim S., & Kim, E.-K. J. (2014). Regular emission characteristics of HFC-134a from mobile air conditioners.  
879 *Journal of Industrial and Engineering Chemistry* **21**: 489-493. <http://dx.doi.org/10.1016/j.jiec.2014.03.009>
- 880 Minnesota Pollution Control Agency (2017). <https://www.pca.state.mn.us/sites/default/files/aq-mvp2-29h.pdf>

- 881 Papasavva, S., Lueckand, D.J., Waterland R.L., Tadonnio, K., & Andersen, S. (2009) Estimated 2017 Refrigerant  
882 Emissions of 2,3,3,3-Tetrafluoropropene (HFC-1234yf) in the United States Resulting from Automobile  
883 Air Conditioning. *Environmental science and technology*. **43**(24):9252-9059
- 884 Schwarz, W. and Harnisch, J. (2003). Establishing the Leakage Rates of Mobile Air Conditioners. Final report for  
885 the EC. Ref. B4-3040/2002/337136/MAR/C1.
- 886 Schwarz, W. and Harnisch, J. (2007). The analysis of the emissions of fluorinated greenhouse gases from  
887 refrigeration and air conditioning equipment used in the transport sector other than road transport and  
888 options for reducing these emissions. Maritime, Rail, and Aircraft Sector.  
889 07010401/2006/445124/MAR/C4. Prepared for the European Commission (DG Environment)
- 890 Schwarz, W. (2012). New Inventory Model Recovery from Old Car Air Conditioners and Emission Factor of  
891 Disposal. Emission Reporting of F-Gases in Refrigeration and Air Conditioning. *Umweltbundesamt Berlin*.  
892 Extract translated from German presentation.
- 893 Umweltbundesamt (2015). Konzept zur Bewertung der technischen Innovationen zur Erfüllung der gesetzlichen  
894 Vorgaben bei stationären Kälte- und Klimaanlageanlagen (Summary in English). ISSN 1862-4359.
- 895 UNEP-TEAP (2016). September 2016 Report of the Technology and Economic Assessment Panel, Volume 2,  
896 Report on the Climate Benefits and Costs of Reducing Hydrofluorocarbons under the Dubai Pathway,  
897 *UNEP Ozone Secretariate*
- 898 Wimberger, E. (2010). Emissions of HFC-134a in Auto Dismantling and Recycling. Contract Number 06-334.  
899 Final Report. Prepared for: *State of California Air Resources Board*.
- 900 Xu, Y., Zaelke, D., Velders, G. J. M., and Ramanathan, V.: The role of HFCs in mitigating 21st century climate  
901 change, *Atmos. Chem. Phys.*, 13, 6083-6089, <https://doi.org/10.5194/acp-13-6083-2013>, 2013.
- 902